



XIAMEN PRODRILL EQUIPMENT CO., LTD

DTH Pipe

CODE	Outer diameter mm	Thread	Wall thickness mm	Length mm	Wrench flat mm	Weight approx kg	Max drilling depth (m)	DTH Hammer size
DP-D76-API2,3/8-T5.5-L1000-WF57	76	2 3/8 API Reg	5.5	1000	57	17	150	4"-6"
DP-D76-API2,3/8-T5.5-L1500-WF57	76	2 3/8 API Reg	5.5	1500	57	22	150	4"-6"
DP-D76-API2,3/8-T5.5-L2000-WF57	76	2 3/8 API Reg	5.5	2000	57	26	150	4"-6"
DP-D76-API2,3/8-T5.5-L3000-WF57	76	2 3/8 API Reg	5.5	3000	57	35	150	4"-6"
DP-D76-API2,3/8-T5.5-L1000-WF65	76	2 3/8 API Reg	5.5	1000	65	17	150	4"-6"
DP-D76-API2,3/8-T5.5-L1500-WF65	76	2 3/8 API Reg	5.5	1500	65	22	150	4"-6"
DP-D76-API2,3/8-T5.5-L2000-WF65	76	2 3/8 API Reg	5.5	2000	65	26	150	4"-6"
DP-D76-API2,3/8-T5.5-L3000-WF65	76	2 3/8 API Reg	5.5	3000	65	35	150	4"-6"
DP-D76-API2,3/8-T6.5-L3000-WF65	76	2 3/8 API Reg	6.5	3000	65	46	150	4"-6"
DP-D76-API2,3/8-T6.5-L4500-WF65	76	2 3/8 API Reg	6.5	4500	65	56	150	4"-6"
DP-D89-API2,3/8-T5.5-L1000-WF65	89	2 3/8 API Reg	5.5	1000	65	20	300	6"-8"
DP-D89-API2,3/8-T5.5-L1500-WF65	89	2 3/8 API Reg	5.5	1500	65	25	300	6"-8"
DP-D89-API2,3/8-T5.5-L2000-WF65	89	2 3/8 API Reg	5.5	2000	65	30	300	6"-8"
DP-D89-API2,3/8-T5.5-L3000-WF65	89	2 3/8 API Reg	5.5	3000	65	40	300	6"-8"
DP-D89-API2,3/8-T6.5-L1000-WF65	89	2 3/8 API Reg	6.5	1000	65	21	300	6"-8"
DP-D89-API2,3/8-T6.5-L1500-WF65	89	2 3/8 API Reg	6.5	1500	65	26	300	6"-8"
DP-D89-API2,3/8-T6.5-L2000-WF65	89	2 3/8 API Reg	6.5	2000	65	32	300	6"-8"
DP-D89-API2,3/8-T6.5-L3000-WF65	89	2 3/8 API Reg	6.5	3000	65	45	300	6"-8"
DP-D89-API2,3/8-T6.5-L4500-WF65	89	2 3/8 API Reg	6.5	4500	65	65	300	6"-8"
DP-D89-API2,3/8-T6.5-L6000-WF65	89	2 3/8 API Reg	6.5	6000	65	84	300	6"-8"
DP-D102-API2,7/8-T6.5-L3000-WF65	102	2 7/8 API Reg	6.5	3000	65	52	500	8"-10"

Remarks: Other specifications are available according to customers' requirements